Letro GT-4 and GTX-4 LED Modules

Four-LED high output modules for deep letters and large light boxes, 12V DC



12V DC · IP65 · 160° lens · 6900K · CE · RoHS

Key specifications

Power per module	**GT-4: 1.44W · GTX-4: 2.0W**
Light output	**GT-4: 230 lm · GTX-4: 320 lm**
LEDs	**4 per module, cool white 6900K**
Supply	**12V DC**
Max spacing (centre to centre)	**GT-4: 350mm · GTX-4: 380mm**
Max modules per run	**GT-4: 20 · GTX-4: 15**
Size (L x W x H)	**GT-4: 45 x 39 x 8.5mm · GTX-4: 62 x 48 x 7.5mm**
Protection	**IP65**
Beam angle	**160°**
Rated life	**35,000 hours at 25°C**

Features

- High output, so fewer modules are needed in deep letters and boxes
- Wide 160° lens
- Wide spacing up to 350mm (GT-4) or 380mm (GTX-4)

Use with

- GT-4: depth 140mm or more
- GTX-4: depth over 170mm
- A 12V DC LED power supply. Total watts = modules x watts per module, plus about 20% spare

Ordering

Option	Light output	Manufacturer part no.	Sign-Tec code
GT-4, 350mm	230 lm	GT-IP-04W69K350	3LED-GT4-IP-04W69K350
GTX-4, 380mm	320 lm	GTX-IP-04W69K380	3LED-GTX4-IP-04W69K380

Data from the NP LED catalogue 2024, pages 9-10 (Neon Products, manufacturer of Letro modules). Figures are typical; the manufacturer may change specifications.