Hansen Neon Flasher, 2 to 6 Channel

Hansen flashers designed to work with Hansen neon convertors and C25 and C50 LED drivers.



Key specifications

Brand / manufacturer	**Hansen**
Voltage	**240V AC 50Hz**
Size	**76 x 76 x 42mm (2 way), 140 x 140 x 76mm (3 and 6 way)**
Manufacturer part no.	**9EVGFL2, 9EVGFL3, 9EVGFL6**
Options	**4 (see ordering)**

Features

- 2 way: 8 programs, 2 x 240V, max 2A per channel, 76 x 76 x 42mm
- 2 way flicker: as above with a flicker (failing neon) program
- 3 way: 14 programs, 3 x 240V, max 1A per channel, 140 x 140 x 76mm
- 6 way: 14 programs, 6 x 240V, max 1A per channel, 140 x 140 x 76mm

Good to know

- Step time is adjustable from 0.25 to 8 seconds per step on every model.
- Rated for outdoor installation when fitted to Hansen's instructions.
- Not for dimmable convertor versions.

Ordering

Channels	Code
2	**9EVGFL2**
2 flicker	**9EVGFL2-Flicker**
3	**9EVGFL3**
6	**9EVGFL6**

Data from the manufacturer, the Sign-Tec catalogue (Feb 2025) and our product records. Figures are typical and the manufacturer may change specifications. Stock varies: check sign-tec.co.uk or call us.